

n				_	_
Р	n	v	v	e	п
•	•	ч	н	•	ч

Horsepower	Requirement	 20	hp

Dimensions

Weight	app. 825 II
Width	30
Height Elevated	72.5
Max Cylinder Height	122
Standard Probe Stroke	52

Hydraulics Requirement

Hydraulic Oil Pressure	2,000 psi
Hydraulic Flow	10 gpm

Hydraulic Operation

Down Force	19,000 lb
Pull-Up Force	24,000 lb
Head Travel Rate Up	15.5 sec
Head Travel Rate Down	12 sec
(With a system pressure of 2,000 psi)	

Hydraulic Hammers

Standard Hammer	- 5K-58	ฮบ ท-เม -	1,200 bpm
Optional Hammer	- BR-87	90 ft-lb -	1,100 bpm

Auger Drive Head

Optional Auger	1	.000 ft-lb
----------------	---	------------

Power Unit Specification	ons
Horsepower	20 hp
Fuel Capacity	4 gal
Engine rpm Setting	3,000 rpm
Power Source	Honda, air cooled V-Twin
Hydraulic Oil Pressure	2,000 psi
Oil Flow	10 gpm
Hydraulic Oil Cooler	18,000 BTU @ 11 gpm
Hydraulic Oil Capacity	12 gal
Weight	540 lb

call for pricing

PowerProbe™ 9100-P



The AMS PowerProbe™ 9100-P is a portable direct push model, designed for use in confined spaces or buildings where a vehicle mounted probe cannot go. This model can be driven off any standard AMS PowerProbe™ with an auxiliary hydraulic hook-up kit, or the optional AMS portable hydraulic power unit. The 9100-P comes standard with a 50 ft-lb hydraulic hammer which can be substituted with a 1,000 ft-lb auger drive head, if small diameter hollowstem augering is what you desire at shallow depths.

Standard Features

- Long lasting powder-coated finish
- Auxiliary hydraulic hook-up
- Anodized metal power track
- Spring loaded pull yoke
- Enhanced control panel
- One year warranty
- Hydraulic valves
- 2 25' hydraulic quick connect hoses
- 50 ft-lb hydraulic hammer


Convenience/Safety Package

- Hand auger to pre-clear soil boring locations
- Hydraulic oil pressure gauge





PowerProbe™ 9100-P



Options and Accessories

- Regen System
- 50' Quck Connect Hose Kit
- 75' Quck Connect Hose Kit

The Mark Mark State of the Stat

Mounting Options

• Truck Hitch Receiver (2")



Hydraulic Power Options

- 9100 Power Unit
- Quick Connect Option

Portable Hydraulic Power Unit

The AMS portable hydraulic power unit is mounted on an easy rolling cart with pneumatic tires and front casters. It has a hydraulic oil cooler and quick connect hydraulic fittings for fast hook up to portable PowerProbes™, grout stations, hydraulic coring drills, and impact wrenches. The power source is a 20 hp air-cooled gas motor with electric start.



The world's finest sampling equipment.